

**SECURE
YOUR WORLD**



WIRES AND CABLES
great-white.in

SecureX^{FR-Pro}

FR-PVC With 105°C base Insulation

Single Core Non-Sheathed 1100V PVC insulation copper conductor cable as per IS 694

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	90 metre		180 metre	
		Rate	Packaging Qty.	Rate	Packaging Qty.
0.5	16/0.2	1075	16	2150	12
0.75	24/0.2	1435	16	2870	12
1	14/0.3	1955	16	3910	12
1.5	22/0.3	2850	12	5700	8
2.5	36/0.3	4585	8	9170	6
4	56/0.3	6805	6	13610	4
6	84/0.3	10095	4	20190	3
10	140/0.3	17265	2	NA	NA
16	126/0.4	27615	2	NA	NA



**SUPERIOR
MULTI
LAYERED
PROTECTION**

SecureX^{FR-Pro}

FR-PVC With 105°C base Insulation

Single Core Non-Sheathed 1100V PVC insulation copper conductor cable as per IS 694 **(HIGHER RATING)**

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	100 metre	
		Rate	Packaging Qty.
25	196/0.4	50428	1
35	276/0.4	69873	1
50	396/0.4	102526	1
70	360/0.5	143745	1



**SUPERIOR
MULTI
LAYERED
PROTECTION**

SecureX^{FR}

FR-PVC With 105°C base Insulation

With a highly flexible class 5 conductor and specially designed Flame Retardant (FR) flexible PVC insulation compound that imparts exceptional flexibility.

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	90 metre		180 metre	
		Rate	Packaging Qty.	Rate	Packaging Qty.
0.75	24/0.20	1410	16	2820	12
1	32/0.20	1885	16	3770	12
1.5	30/0.25	2750	12	5500	8
2.5	50/0.25	4425	8	8850	6
4	56/0.30	6735	6	13470	4
6	84/0.30	9995	4	19990	3




**SUPERIOR
MULTI
LAYERED
PROTECTION**

SecureX^{FRLSH-Pro}

FR-LSH With 105°C base Insulation

With all properties of FR, the insulation of SecureX Plus Cables is further fortified with low smoke and low halogen emission characteristics

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	90 metre		180 metre	
		Rate	Packaging Qty.	Rate	Packaging Qty.
1	14/0.30	2055	16	4110	12
1.5	22/0.30	2990	12	5980	8
2.5	36/0.30	4815	8	9630	6
4	56/0.30	7145	6	14290	4
6	84/0.30	10600	4	21200	3
10	140/0.30	18130	2	NA	NA
16	126/0.40	28995	2	NA	NA



**FLAME
RETARDANT
LOW
SMOKE**

SecureX^{FRLSH}

FR-LSH With 105°C base Insulation

With a highly flexible class 5 conductor and specially designed Flame Retardant with low smoke and low halogen emission characteristics (FR-LSH) flexible PVC insulation compound that imparts exceptional flexibility.

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	180 metre	
		Rate	Packaging Qty.
1	32/0.20	3970	12
1.5	30/0.25	5770	8
2.5	50/0.25	9290	6
4	56/0.30	14150	4
6	84/0.30	20990	3



**FLAME RETARDANT
LOW SMOKE**

SecureX^{ZHFR-Pro}

ZHFR With 105°C base Insulation

Single Core Crosslinked (HFI-XL 70) & Thermoplastic (HFI-TP 70) Insulated Unsheathed 1100 Volts, Copper Conductor Cable as per IS 17048

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	180 metre	
		Rate	Packaging Qty.
1	14/0.3	4290	12
1.5	22/0.3	6202	8
2.5	36/0.3	9838	6
4	56/0.3	14704	4
6	84/0.3	21810	3

Sq.mm	Nos. / Nom Diameter Of Wire Nos. / mm	90 metre	
		Rate	Packaging Qty.
10	140/0.3	18676	2
16	126/0.4	29859	2



**ZERO HALOGEN
FLAME RETARDANT**



LAYER PROTECTION



HIGHER CURRENT CAPACITY




FLAME RETARDANT



BASE INSULATION

Round Multi-Core Cables
1100V PVC Insulated & Sheathed Industrial Cable As per IS 694

Sq.mm	Nos./ Nom Diameter Of Wire Nos. / mm	FR-100 metre Rate		
		2 core	3 core	4 core
0.5	16/0.20	3439	4632	5938
0.75	24/0.20	4688	6428	8098
1	32/0.20	5756	7947	10339
1.5	30/0.25	7801	10900	14554
2.5	50/0.25	12388	17769	23219
4	56/0.30	19008	27172	36440
6	84/0.30	27683	40020	53454
10	140/0.30	47636	68927	92009
16	126/0.40	75941	110479	145736



ROUND MULTI-CORE CABLES

Flat Three Core

GreatWhite Flat Submersible Cables are made with tailor- made PVC compound, designed to prevent water ingress, and perform for years under water.

Sq.mm	Nos./ Nom Diameter Of Wire Nos. / mm	100 metre
		3 core Rate
1.5	22/0.3	11548
2.5	36/0.3	18593
4	56/0.3	27016
6	84/0.3	40009
10	80/0.4	67808
16	126/0.4	110533



FLAT SUBMERSIBLE CABLES

Supplied in 100m Polybag Packing
 *Longer Length in Multiple of 100m can be supplied upto 100m

Telephone & Switch Board Cable

No. Of Pairs & Size	0.4 mm			0.5 mm		
	No Dia mm	Rate (100M)	Std Pkg	No Dia mm	Rate (100M)	Std Pkg
1 Pair	2.4	1042	12	3.1	1450	12
2 Pair	3.1	1636	8	3.9	2412	8
3 Pair	3.5	2368	6	4.2	3647	6
4 Pair	3.9	3008	6	5.1	4770	6
5 Pair	4.3	3854	4	5.6	5795	4



TELEPHONE CABLES

Co-Axial Cable (Gas Injected Physical Foam)

Standard Packing Coil Length m	RG 6	RG-6F CCS	Std Pkg
	100	3555	2162
305	10741	6595	1



CO-AXIAL CABLE

CAT 6 300MHZ

Standard Packing Coil Length m	Rate	Std Pkg
	100	5479
305	16703	1



LAN CABLES



GreatWhite Global Pvt. Ltd.
13th Floor, B-Wing, Peninsula Business Park, Senapati Bapat Marg, Lower Parel (W), Mumbai 400 013.
Tel: 022 300 36565, E-mail: info@great-white.in, Web: www.great-white.in